

Filters

- Filters to 3 micron
- Anodized Aluminum housing with manual or auto drain
- Threaded bowl for 1/4" to 1/2" sizes
- Optional sight glass available
- Economic and durable



Model Number with auto drain*	Flow (SCFM)	Maximum Supply Pressure (PSIG)	Port Size (NPT)	Maximum Operating Temp (°F)	Weight (lb.)	Dimensions (in.) Diameter x Height
F250HDMF	30	250	1/4"	200	3.0	2.5 x 6.5
F380HDMF	75	250	3/8"	200	3.0	2.5 x 6.5
F500HDMF	85	250	1/2"	200	3.0	2.5 x 6.5
F750HDMF	175	250	3/4"	200	4.0	3.8 x 8.0
F1000HDMF	240	250	1"	200	4.0	3.8 x 8.0
F1250HDMF	320	250	1 1/4"	200	4.5	4.0 x 10.5
F1500HDMF	400	250	1 1/2"	200	4.5	4.0 x 10.5

*For model with manual drain, replace "F" with "P". For model with optional sight glass, add "T" to end of model number.

Lubricators

- Rugged, heavy duty high-flow design
- Anodized Aluminum housing
- Siphon tube filter provides clean lubricant downstream
- Twist-off easy bowl removal
- Adjustable oil feed with tamper-proofing capability
- Can be filled while under pressure
- 1/4" through 1 1/2" NPT ports available



Model Number	Flow (SCFM)	Maximum Supply Pressure (PSIG)	Port Size (NPT)	Maximum Operating Temp (°F)	Weight (lb.)	Dimensions (in.) Diameter x Height
L250HDM	40	250	1/4"	200	3.0	2.5 x 6.9
L380HDM	100	250	3/8"	200	3.0	2.5 x 6.9
L500HDM	120	250	1/2"	200	3.0	2.5 x 6.9
L750HDM	190	250	3/4"	200	4.0	3.8 x 11.3
L1000HDM	270	250	1"	200	4.0	3.8 x 11.3
L1250HDM	600	250	1 1/4"	200	4.5	4.0 x 11.6
L1500HDM	750	250	1 1/2"	200	4.5	4.0 x 11.6